

25 Year System Warranty

(International) DS-025.0INTL-0720

Globally Proven Construction Solutions

APPLICATION	PRODUCTS
Underlayment	NXT™ Primer
	NXT Level Plus
Floor Warming [^]	STRATA_HEAT™ Wire
	STRATA_HEAT
Vapor Reduction	NXT Vapor Reduction Coating
Waterproofing/ Anti-Fracture	HYDRO BAN®
	HYDRO BAN Sheet Membrane
	9235 Waterproofing Membrane
	LATAPOXY® Waterproof Flashing Mortar
Shower System	HYDRO BAN Pre-Sloped Shower Pan (and applicable accessories)
	HYDRO BAN Linear Pre-Sloped Shower Pan (and applicable accessories)
	HYDRO BAN Shower & HYDRO BAN Shower Kits (and applicable accessories) HYDRO BAN Linear Drain (and applicable accessories)
	HYDRO BAN Bonding Flange Drain (and applicable accessories)
	HYDRO BAN Board (and applicable accessories)
Sound Control/	125 TRI MAX®
Anti-Fracture	
Plaza & Deck	Plaza and Deck System
Thick Bed Method	3701 Fortified Mortar
	3701 Mortar Admix mixed with 226 Thick Bed Mortar
Slurry Bond Coat	254 Platinum
	4237 Latex Additive mixed with any of the following:
	 211 Powder; or
	 317 Mortar
Thin Bed Method	254 Platinum (regular or rapid version)
Thin bed method	MULTIMAX™ Lite
	LATAPOXY [®] 300 Adhesive OR BIOGREEN™ 300
	Glass Tile Adhesive Mortar
	4237 Latex Additive mixed with any of the following;
	 211 Powder; or
	 317 Mortar
	325 Premium Tile Adhesive mixed with 333 Flexible Additive
Spot Bonding	LATAPOXY 310 Stone Adhesive - Standard and Rapid Grade
MVIS	MVIS Air & Water Barrier MVIS Premium Mortar Bed
	MVIS Premium Mortar
	MVIS Premium Pointing Mortar
Grouting	SPECTRALOCK® PRO Premium Grout (non-industrial applications)
	SPECTRALOCK 2000 IG
	LATAPOXY SP-100
	PERMACOLOR® Grout
	PERMACOLOR Select
Sealant [†]	LATASIL™ LATASIL 2442 D
	LATASIL 9118 Primer

[†] Use of suitable flexible sealant is required per Tile Council of North America Detail EJ171 for use in expansion joints, coves, corners, changes in plane and other joints or wherever tile or stone abuts dissimilar materials or restraining surfaces.

[^] Floor Warming and STRATA_HEAT Thermostat sold by LATICRETE International, Inc. warrants parts and materials for one (1) year from the date of purchase. The sole remedy for the Thermostat is product replacement (see DS 230.13 for full details on the LATICRETE[®] Product Warranty).

LIMITED WARRANTY

Subject to the conditions and limitations stated below, LATICRETE INTERNATIONAL, INC. ("LATICRETE") warrants that the products listed on this document will be free from manufacturing defects and will not break down or deteriorate under normal usage for a period of twenty-five (25) years from the date of purchase when installed in accordance with the written specifications of LATICRETE and industry standard guidelines. For this limited warranty to apply, the applications that comprise the installation must be performed with the products listed in this document for each application (refer to chart).

Notwithstanding the previous paragraphs, exterior facades with ceramic tile, stone, adhered masonry veneer, or thin brick installed over substrates with steel or wood framing do not qualify for this limited warranty—see Data Sheet 230.15 for such applications.

DISCLAIMER

THIS LIMITED WARRANTY IS GIVEN IN LIEU OF ANY OTHER WARRANTY, EXPRESS OR IMPLIED. THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES BASED ON SAMPLES OR ORAL STATEMENTS, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE OF THIS DOCUMENT. IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED.

EXCLUSIVE REMEDY

The sole and exclusive remedy for a breach of this limited warranty is replacement of only the specific portion of the installation that is proven to be defective**. LATICRETE will pay for replacement of its own products and replacement of finishing materials, as well as for labor for the replacement installation, but LATICRETE will not pay more, calculated on a square-foot (square-meter) basis, for the replacement than the original purchase price of the portion being replaced.

LATICRETE will not pay for replacement of any portion of the installation that is not proven to be defective.

In the event that the sole and exclusive remedy described above fails of its essential purpose, the liability of LATICRETE is limited to the monetary value, on a square-foot (square-meter) basis, of the original purchase price of the portion being replaced.

**NOTE: Efflorescence is a normal condition of portland cement mortars and is not a defective condition.

EXCLUSIONS

LATICRETE is not responsible for workmanship not in accordance with the instructions of LATICRETE and industry standard guidelines. Cracking due to structural movement, excessive deflection or other failure in the substrate is also not covered.

LATICRETE IS NOT LIABLE FOR ANY INCIDENTAL DAMAGES OR CONSEQUENTIAL DAMAGES, INCLUDING LOSSES DUE TO DELAYS, INCURRED BY THE PURCHASER OR ANY OTHER PARTY.

NO ASSIGNMENT

This limited warranty is not transferable or assignable.

HOW TO MAKE A CLAIM

To make a claim under this limited warranty, you must notify LATICRETE in writing within thirty (30) days of the discovery of the alleged manufacturing defect. At the option of LATICRETE, you may be required, as a condition of this limited warranty, to provide proof of product purchase and use.

Address your claim to:

LATICRETE International, Inc. 1 LATICRETE Park North Bethany, CT 06524-3423 USA Attn.: Technical Services Department

TECHNICAL INFORMATION

Technical assistance and information is available by calling the LATICRETE Technical Services Line:

Toll Free:	1.800.243.4788, ext. 1235
Telephone:	+1.203.393.0010, ext. 1235
- ·	1 000 000 1010

Fax: +1.203.393.1948

LATICRETE International, Inc.

One LATICRETE Park North, Berhany, CT 06524-3423 USA = 1.800.243.4788 = +1.203.393.0010 = www.laticrete.com ©2020 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.