

DUPONT™STONETECH® PROFESSIONAL GROUT RELEASE

TECHNICAL DATA SHEET



PRODUCT BENEFITS

- Makes grout clean-up during installation easier
- · Prevents grout from staining stone
- Water-based coating
- Interior and exterior use

RECOMMENDED SURFACES

Natural stone such as marble, limestone, travertine, slate, sandstone and tumbled stone.

Masonry and concrete.

Not recommended for use on ceramic tile and dense (low absorbency) stone.

AVAILABLE SIZES

Gallon

COVERAGE

Up to 1,700 sq ft per gallon, depending on porosity of surface.

TECHNICAL INFORMATION

Form: Liquid Specific Gravity: 1.00 HMIS Rating: 2,0,0

Flash Point: $>230 \, ^{\circ}\text{F} \, (110 \, ^{\circ}\text{C})$ Freeze Point: $32 \, ^{\circ}\text{F} \, (0 \, ^{\circ}\text{C})$

pH: 12

VOC CONTENT

<400 g/L (excluding water) for EPA purposes.

<120 g/L (including water) for U.S. state purposes (Low Solids Coating).

DIRECTIONS

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of application and desired results. Make sure surface is clean, dry and free of loose debris. Surface temperature should be between 50 °F and 80 °F (10 °C and 26.7 °C). Avoid skin and eye contact. Wear protective eyewear, gloves, long sleeves, and long pants while handling product. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area until foot traffic resumes.

- Mask off any surfaces not intended to be treated
- Apply an even coat with a paint pad, paintbrush, paint roller or low-pressure sprayer.
- 3. Allow Grout Release to completely penetrate the surface for 5–15 minutes.
- Wipe up all remaining sealer from the surface. Do not allow excess liquid to pool or dry on the surface. Do not over apply.
- 5. Allow for a minimum of 4 hours cure time prior to grouting.
- After grouting, remove excess grout.
 Do not allow grout to completely dry prior to removal.
- 7. Clean equipment with water.

STORAGE AND HANDLING INSTRUCTIONS

CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE RESPIRATORY IRRITATION. Do not ingest. Avoid contact with eyes and skin. Avoid prolonged exposure to vapors. Use in a well-ventilated area. KEEP OUT OFTHE REACH OF CHILDREN. Do not freeze or store above 100 °F/38 °C. Do not mix with other chemicals.

EMERGENCY/FIRST AID PROCEDURES

Ingestion: Do not induce vomiting. Call poison control center. Call a physician.

Inhalation: Remove affected person to fresh air. Call a physician if respiratory irritation persists.

The DuPont™ StoneTech® Professional product line complies with all federal, state and local VOC regulatory requirements and is packaged in containers with at least 25% post-consumer recycled material.

DuPont™ StoneTech® Professional 2520 Barrington Court Hayward, CA 94545

Technical Support: 888-786-6343 Customer Service: 877-786-6383

www.stonetechpro.com



The miracles of science™

The information is furnished free of charge and based on information that DuPont believes to be generally reliable and accurate. Individual facts and circumstances may differ. It is intended for your use at your own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Copyright © 2014 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™, and StoneTech® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.